MATERIAL DATA SAFETY SHEET

SECTION I

MANUFACTURER'S NAME STREET ADDRESS CITY, STATE & ZIP EMERGENCY TELEPHONE

Parks Corporation One West Street Fall River, MA 02720 (508) 679-5938 CHEMICAL FAMILY

CHEMICAL FAMILY
TRADE NAME

Refinisher N.A.

PARKS FURNITURE REFINISHER

Gallon #1723 Quart #1725

Less than 1

FORMULAS N.A. REVISED 09/08/94

SECTION II – HAZARDOUS INGREDIENTS

SIZES/CODES

PAINTS, PRESERVATIVES & SOLVENTS

SOLVENTS	CAS#	<u>%</u>	PPM <u>TLV</u>	<u>PEL</u>
Acetone (DiMethyl Ketone)	67-64-1	15-45	750	1000
*Methanol (Methyl Alcohol)	67-56-1	15-35	200	200
IPA (IsoPropyl Alcohol)	67-63-0	15-35	400	400
*Toluol (Toluene)	108-88-3	15-35	100	200

*SARA listed chemical

PIGMENTS: N.A.

CATALYST: N.A.

VEHICLE: N.A.

ADDITIVES & OTHERS: N.A.

SECTION III – PHYSICAL DATA

BOILING POINT (°F)133°FSPECIFIC GRAVITY ($H_2O = 1$)0.815VAPOR PRESSURE100.74 mmHgPERCENT VOLATILE100%

VAPOR DENSITY (AIR = 1) Heavier BY VOLUME (%)
SOLUBILITY IN WATER Moderate EVAPORATION RATE

APPEARANCE Clear (ETHER = 1)

ODOR Aromatic V.O.C. 804 g/l

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): TAG CC 19°F

FLAMMABLE LIMITS: Unknown.

EXTINGUISHING MEDIA: Water, dry chemical, fog, regular foam.

SPECIAL FIRE FIGHTING PROCEDURES: Do not use straight water stream to extinguish fire. Use self-contained breathing

apparatus equipped with positive pressure mode.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks and open flame.

SECTION V – HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II.

EFFECTS OF OVEREXPOSURE: Causes irritation of eyes and skin. Prolonged contact with skin can cause defatting and dermatitis. Excessive inhalation of vapors can cause nasal and respiratory irritation, headache, dizziness, nausea and unconsciousness.

REVISED: 09/08/94

SECTION V – HEALTH HAZARD DATA (CONT'D)

EMERGENCY AND FIRST AID PROCEDURE

EYE CONTACT: Flood with plenty of water and get medical attention.

SKIN CONTACT: Flush with water and soap.

INHALATION: Remove patient to fresh air if breathing is difficult and call physician.

SWALLOWING: Get medical attention promptly.

SECTION VI - REACTIVITY DATA

STABILITY: Stable.

CONDITIONS TO AVOID: Keep away from sparks and open flame.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents (e.g., Chromates, Permanganates, Strong Alkalies, Nitric Acid).

HAZARDOUS DECOMPOSITION PRODUCTS: May release toxic fumes if in contact with open flame.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Keep away from sparks and open flame.

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep away from open flame, sparks and hot surfaces. Do not smoke or allow others to do so. Wash with water and detergents. Wear self-breathing apparatus. Large spills can be taken on sand, earth, clay, floor absorbents and shoveled into containers for disposal. Prevent runoff to sewers, streams or other bodies of water.

WASTE DISPOSAL METHOD: Dispose of per local, state and federal regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFIC TYPE): Approved respiratory mask.

VENTILATION

LOCAL EXHAUST: Yes.

MECHANICAL (GENERAL): Yes.

SPECIAL: No smoking.

OTHER: Must have adequate ventilation.

PROTECTIVE GLOVES: Rubber gloves.

EYE PROTECTION: Protective goggles.

OTHER PROTECTIVE EQUIPMENT: Use protective clothing against splash and spills. Eyewash. Shower.

SECTION IX – STORAGE AND SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store near open flame or elevated temperature.

OTHER PRECAUTIONS: Cannot be made nonpoisonous. Prevent prolonged or repeated breathing of vapor or spray mist.

REVISED: 09/08/94

SECTION IX - STORAGE AND SPECIAL PRECAUTIONS (CONT'D)

<u>OTHER REGULATORY INFORMATION</u>: The State of California's Safe Drinking Water and Toxic Enforcement Act of 1986 (Prop 65) develops a list of chemicals that require specific warnings relating to cancer and/or reproductive toxicity. This product contains the following chemicals subject to the reporting requirements of the State of California's Safe Drinking Water and Toxic Enforcement Act of 1986 (Prop 65).

 CHEMICAL
 CAS #
 QUANTITY

 Benzene*
 71-43-2
 <20 PPM</td>

 Toluol
 See Section II
 See Section II

The warning on the product states:

WARNING: USE OF THIS PRODUCT WILL EXPOSE YOU TO BENZENE WHICH IS KNOWN TO CAUSE CANCER AND TO TOLUOL WHICH IS KNOWN TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

THE INFORMATION IN THIS DOCUMENT IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT OR THE HAZARDS RELATED TO ITS USE. THIS INFORMATION AND PRODUCT ARE FURNISHED ON THE CONDITION THAT THE PERSON RECEIVING THEM SHALL MAKE HIS OWN DETERMINATION AS TO THE SUITABILITY OF THE PRODUCT FOR HIS PARTICULAR PURPOSE AND ON THE CONDITION THAT HE ASSUME THE RISK OF HIS USE THEREOF.

^{*}Not included in Section II as this chemical is less than .1% of the formula.